

AMENDMENTS TO THE CLAIMS

Please amend the claims in accordance with the changes indicated in the complete listing of claims that follows, which shall replace all prior versions of the claims in the application.

1. **(Currently Amended)** A multi-level chair for supporting a post-tension concrete reinforcement cable at a fixed height from a bottom of a concrete form, said multi-level chair comprising:

a body including a plurality of receptacles, the plurality of receptacles comprising a ~~vertically-oriented array of at least three~~ receptacles positioned at different and equally spaced ~~apart~~ heights from the bottom of the concrete form, said receptacles ~~in the array being spaced at a fixed vertical interval and~~ being adapted to support a post-tension reinforcement cable of a predetermined diameter.

2. **(Original)** The multi-level chair of claim 1 wherein said body is injection molded plastic.

3. **(Original)** The multi-level chair of claim 1 wherein said body has an inverted V-shape including a pair of legs extending downwardly from an apex of said body.

4. **(Original)** The multi-level chair of claim 3 wherein said receptacles are at staggered heights along said legs.

5. **(Original)** The multi-level chair of claim 3 wherein said chair is nestably stackable.

AMENDMENT AFTER FINAL ACTION

Appln. No. 10/713,444

Docket No. 442005-00108

6. **(Currently Amended)** A multi-level chair for supporting a post-tension concrete reinforcement cable at a fixed height from a bottom of a concrete form, said multi-level chair comprising:

an inverted V-shaped body having a pair of legs extending downwardly from an apex of said body, said body including multiple receptacles comprising ~~a vertically oriented array of at least three~~ receptacles positioned at different and equally spaced apart heights from the bottom of the concrete form along at least one of said legs, each of said receptacles ~~in the array being spaced at a fixed vertical interval and~~ being sized to support said post-tension reinforcement cable so that a user may place said post-tension cable in a selected one of said receptacles.

7. **(Original)** The multi-level chair of claim 6 wherein said body is injection molded plastic.

8. **(Original)** The multi-level chair of claim 6 wherein said receptacles are identically sized.

9. **(Currently Amended)** The multi-level chair of claim 6 wherein said receptacles are vertically spaced apart from each other one-quarter inch.

10. **(Original)** The multi-level chair of claim 6 wherein said receptacles are adapted to receive the same gauge cable.

11. **(Original)** The multi-level chair of claim 6 wherein said chair may be nestably stacked on top of a second multi-level chair.

AMENDMENT AFTER FINAL ACTION

Appln. No. 10/713,444

Docket No. 442005-00108

12. **(Currently Amended)** A multi-level chair for supporting a concrete reinforcement cable under tension at a fixed height from a bottom of a concrete form, said multi-level chair comprising:

an inverted V-shaped body having a pair of legs extending downwardly from an apex of said body, each of said legs having a fixed length and multiple receptacles comprising a ~~vertically oriented array of at least two~~ receptacles, ~~said receptacles in the array being spaced at a fixed vertical interval and~~ positioned at different heights from the bottom of the concrete form along said length of said leg for supporting said reinforcement cable, wherein said multiple receptacles of one of said legs are positioned at different heights with respect to said multiple receptacles of the other of said legs and wherein a user may support said reinforcement cable in a selected receptacle.

13. **(Original)** The multi-level chair of claim 12 wherein said body is injection molded plastic.

14. **(Original)** The multi-level chair of claim 12 wherein each of said legs terminates in a foot.

15. **(Withdrawn)** The multi-level chair of claim 14 wherein said feet are joined by a base plate.

16. **(Original)** The multi-level chair of claim 12 wherein said receptacles are spaced from each other one-half inch along each of said legs.

17. **(Original)** The multi-level chair of claim 12 wherein said receptacles are adapted to receive the same gauge cable.

AMENDMENT AFTER FINAL ACTION

Appln. No. 10/713,444

Docket No. 442005-00108

18-20. (Canceled)

21. (**Withdrawn – new**) A multi-level chair for supporting a post-tension concrete reinforcement cable at a fixed height from a bottom of a concrete form, said multi-level chair comprising:

a body including a pair of opposing sidewalls defining a downwardly extending slot, said slot including a plurality of receptacles comprising at least three receptacles positioned at different and equally spaced apart heights from the bottom of the concrete form, said receptacles being adapted to support a post-tension reinforcement cable of a predetermined diameter, and said slot having a width that is less than said predetermined diameter, wherein said post-tension reinforcement cable is retainable within a selected receptacle.

22. (**Withdrawn – new**) A multi-level chair for supporting a post-tension concrete reinforcement cable at a fixed height from a bottom of a concrete form, said multi-level chair comprising:

a body including a pair of opposing sidewalls defining a plurality of receptacles comprising at least three receptacles positioned at different and equally spaced apart heights from the bottom of the concrete form, said receptacles being adapted to support a post-tension reinforcement cable of a predetermined diameter and being connected to adjacently spaced receptacles by non-vertical slot segments having a width that is less than said predetermined diameter, wherein said post-tension reinforcement cable is retainable within a selected receptacle.